

# Request a Straight Stair Quote

Getting a quote for a York Straight Stair is easy. You can submit a request online or simply complete and fax or mail the information below. It takes seven to ten days to return your quote through the U.S. Mail.

If you have any questions about requesting a quote, please call 1-800-996-5558 or e-mail us at [info@yorkspiralstair.com](mailto:info@yorkspiralstair.com). Please fax this completed form to 207-872-6731 or mail to:

York Spiral Stair  
720 Main Street  
Vassalboro, ME 04989

Your Contact Information (required)	Shipping Information (required)
Name _____	Job Site Name _____
Street _____	Shipping Address _____
City _____ State _____ Zip _____	City _____ State _____ Zip _____
Phone _____	Job Phone _____
E-mail _____	E-mail _____

## York Straight Stair Specifications (required)

**Note:** CHECK ONE BOX ONLY.

1. Tread width of stair required:  36"  44"  Other custom width \_\_\_\_\_

2. Finished floor to floor height: \_\_\_\_\_

3. Total stair run: \_\_\_\_\_

4. Species:  Red Oak  Mahogany  Ash  Maple  Hickory  
 Cherry  Walnut  Teak  Poplar (Paint Grade)

**Note:** IF YOU'D LIKE STAIRS BUILT WITH A COMBINATION OF WOOD SPECIES, PLEASE CALL US TO DISCUSS.

5. Finish:  Without  Clear Finish

6. Balusters:  7/8" Round  1 1/8" Square (side mounted)  1 1/8" Square (top mounted)

7. Baluster spacing:  6" On Center  4 3/4" On Center  3", 4 3/4", 3" On Center

8. Handrails:  Right (descending)  Left (descending)  
 Both right and left

9. Handrail size:  1 1/2" x 3 1/2" (standard)  
 1 1/2" x 5 1/2" (custom—required for all stairs with square, side mounted balusters)  
 Single Finger Groove on 1 1/2" x 5 1/2" (custom)  
 Double Finger Groove on 1 1/2" x 5 1/2" (custom)

10. Risers:  Open Risers  Partial Risers  Solid Risers

**York Upper Floor Components Needed** (optional)

1. Unbored handrail:       Straight      Linear feet required \_\_\_\_\_  
    Curved      Linear feet required \_\_\_\_\_  
    Not required
2. Unbored nosing:       Straight      Linear feet required \_\_\_\_\_  
    Curved      Linear feet required \_\_\_\_\_  
    Not required
3. Fascia board:       Straight      Linear feet required \_\_\_\_\_  
    Curved      Linear feet required \_\_\_\_\_  
    Not required
4. Newel post:       3" x 3" x 44"      Amount required \_\_\_\_\_  
    1<sup>7</sup>/<sub>8</sub>" x 1<sup>7</sup>/<sub>8</sub>" x 44"      Amount required \_\_\_\_\_  
    Other \_\_\_\_\_      Amount required \_\_\_\_\_  
    Not required
5. Half newel post:       1<sup>1</sup>/<sub>2</sub>" x 3" x 44"      Amount required \_\_\_\_\_  
    1<sup>5</sup>/<sub>16</sub>" x 1<sup>7</sup>/<sub>8</sub>" x 44"      Amount required \_\_\_\_\_  
    Other \_\_\_\_\_      Amount required \_\_\_\_\_  
    Not required
6. Rosette:       Oval      Amount required \_\_\_\_\_  
    Designer      Amount required \_\_\_\_\_  
    Not required
7. Baluster:       7/8" Round      Amount required \_\_\_\_\_  
    1<sup>1</sup>/<sub>8</sub>" Square      Amount required \_\_\_\_\_  
    Not required
8. Knee wall cap:       Straight      Linear feet required \_\_\_\_\_  
    Curved      Linear feet required \_\_\_\_\_  
    Not required
9. Steel anchor plates for  
concrete installation:       Required       Not required

**Please Note:** Your local building code officials may require that your stairs be built with closer baluster spacing, partial risers, handrails that have finger grooves, and/or a tread width of at least 26". Local code officers often have different interpretations of the national building codes, and some municipalities may have their own specific handrail, baluster, and riser code requirements. Often times, the local code requirements for a secondary stair, or a stair that serves an open loft area, will be much less stringent. **Please consult with your local building inspector or code officer for information with respect to your local code requirements.**